



The **LMB520 bollard** is a **high-performing** lighting solution with a **durably constructed** design. It features an internally reinforced steel structure, making it ideal for areas that require both reliable lighting and sturdy construction.

# BOLLARD LMB520

### Bollard Construction;

Cast aluminum base cover and top attached to extruded aluminum core internally reinforced with steel rods to withstand lateral impact loads.

Size: Diameter 8.25"

Height: 24"- 42"

### Mounting Details;

Base Plate: Galvanized Steel

Bolt circle Diameter: 5.25" - 6.25"

Anchor Bolts: 4 x 3/8" Dia x 10" long Galv. steel

### Lighting Specifications

Lumens: 700-2500 Alms. (Delivered)

CCT: 3000-4000K CRI > 70

RGBW option available

Lighting Distribution: IES2, IES3, IES5

### Electrical specifications;

Power Source: LED Driver (Electronic HPF)

Voltage: 120-277, and 347-480V

SURGE SUP: 20kVA

Power: 10-40W

### Lighting Controls;

0-10 Dimming

### Emergency Power;

500 Lumens (Delivered) for 90 minutes (Integral Battery Pack)

### Chromaticity;

High output LEDs come standard 3000K & 4000K (+/- 300K) minimum nominal 70 CRI. Additional CCT emitters are available upon request.

### Finish;


Housing is finished with 5 stages of pre-paint procedure prior to Electrostatically Thermoset Powder-Coat application. Standard colors are Bacardi Black, Dk Bronze, Platinum Grey, Galactic Green, and Snow White.

### Certification;

ETL certificate to UL 1598 / CSA C22.2 No 250.0

### Warranty;

LMB520 Bollard comes with a 5 year Limited warranty on all electronic and electrical components



**COMPLY TO**  
**UL1598 / CSA C22.2 No**  
**250.0**  
**WARRANTY**  
**5 YEARS**

## ORDERING INFORMATION

LMB520-36	T3	3K	L1	LV	PC	DS	GG
Model	Light Distribution	CCT	Lumens (Initial)	Input Voltage	Lighting Control	Options	Finish
LMB520-24	T2-IES 2	3K-3000K	L1 - 1000Lm	LV—120V	LD -0-10V DIM	RC-Rigid Centre	BB-Bacardi Black
LMB520-30	T3-IES3	4K-4000K	L2 - 1500Lm	UV- 120-277V	PC- Photocell	CB-RGB Centre	DB-Dk Bronze
LMB520-36	T5-IES 5	5K-5000K	L3- 2000lm	HV- 347 V	DM—DMX	EM-Open Centre	PG-Platinum Grey
LMB520-42			L4 - 2500Lm*				GG -Galactic Green
			For T5 Only				SW-Snow white